

Fiber Transition Housings, FTH-76S

1 SC Simplex adapter, slack routing spool & splice holder, ground post, 10 meters slack storage, hex screw

CORNING

Corning fiber transition housing (FTH) provides an optical demarcation and interconnection point for fiber-to-the-premises (FTTP) applications. Suitable for indoor or outdoor locations, the FTH provides physical protection for the transition between provider and customer, and facilitates system testing.

Fiber entering and exiting the housing may be secured using the internal lances with the tie wraps. Slack cable is held neatly and securely within the housing.

The housings are molded from an engineering grade thermoplastic selected to withstand harsh outdoor environments. These housings may be installed on a wall or secured to a vertical conduit. Unauthorized access is deterred by the security screw latch. For added security, a lock may be installed on the integrated locking hasp.

Features and Benefits

Multiple fiber termination options

Supports SC APC and OptiTap® Connector adapters as well as fusion splicing

Slack storage

Provides up to 10 m of slack storage (dependent upon type of cable installed)

Weather-resistant housing design

Fiber and connections protected for long life

Standards

Approvals and Listings

UL-Listed to United States and Canadian safety standards

Design and Test Criteria

Tested to Telcordia standards

Specifications

Design - Hardware	
Number of Adapters	1
Ground Configuration	Ground Post
Fiber Management Configuration	Slack routing spool with splice holder
Security Fasteners	Standard 3/8-in hex screw



Fiber Transition Housings, FTH-76S

1 SC Simplex adapter, slack routing spool & splice holder, ground post, 10 meters slack storage, hex screw



Mechanical Characteristics

Dimensions (HxWxD)	25.9 cm x 21.6 cm x 7.6 cm (10.2 in x 8.5 in x 3.0 in)
Weight	0.5 kg (1.1 lb)

Ordering Information

Part Number	FTH-76S-A0200
Product Description	Fiber Transition Housing, FTH-76S Housing, 1 SC Simplex adapter, slack routing spool & splice holder, ground post, 10 meters slack storage, hex screw
EAN Code	4056418169996

Shipping Information

Dimensions (HxWxD)	41.9 cm x 38.1 cm x 27.3 cm (16.5 in x 15 in x 10.7 in)
Shipping Weight	5.0 kg (11 lb)
Units per Delivery	10/1

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

